

## DOME CAMERA

- TP-100VDC** 1/3" Color Dome Camera with Vari-focal Lens  
**TP-200VDC-P** 1/3" High Resolution Color Dome Camera with Vari-focal Lens  
**TP-535VDC** 1/3" Super-High Resolution Color Dome Camera with Vari-focal Lens



TP-535VDC



TP-100VDC  
TP-100VDC-M



TP-200VDC-P

### FEATURES:

- With 3-Gon Triangle Dome case to attract user's attention
- With built-in Advanced High Speed 3.8~9.5mm F1.2 Aspherical Auto Iris lens (TP-535VDC, TP-100/200VDC), 4~9mm varifoal lens (TP-100VDC-M, TP-200VDC-P)
- Different selection for Standard resolution (420 TVL) or High resolution (480 TVL) or Super-high Resolution(535 TVL).

SPECIFICATIONS			
MODEL	TP-535VDC	TP-200VDC-P	TP-100VDC TP-100VDC-M
PICK-UP DEVICE	1/3 " Interline Transfer CCD		
SYNC SYSTEM	Internal sync		
PICTURE ELEMENTS	NTSC: 768(H)x494(V) PAL: 752(H)x582(V)	NTSC: 768(H)x494(V) PAL: 752(H)x582(V)	NTSC: 510(H)x492(V) PAL: 500(H)x582(V)
HORIZONTAL RESOLUTION	535 TV Lines	480 TV Lines	420 TV Lines
GAMMA CORRECTION	0.45		
BACK LIGHT COMPENSATION	On/Off switch	Auto	On/Off switch
AUTO GAIN CONTROL	High/Low Switch	Auto	High/Low (TP-100VDC) Auto (TP-100VDC-M)
AUTO WHITE BALANCE	Auto		
LENS	3.8~9.5mm/F1.2~360	4~9 mm / F1.5	TP-100VDC 3.8~9.5 mm TP-100VDC-M 4~9 mm
IRIS LEVEL	Adjustable		
S/N RATIO	Over 48 dB		
VIDEO OUTPUT	1.0 Vp-p, 75 ohm		
MINIMUM ILLUMINATION	0.5LUX/F1.2	0.4LUX/F2.0	0.2LUX/F2.0 (TP-100VDC) 0.4LUX/F2.0 (TP-100VDC-M)
POWER SOURCE	DC 12V ± 10%		
POWER CONSUMPTION	5W max.	120mA max.	120mA max.
WORKING TEMPERATURE	0 to +40	-10 to +50	-10 to +50
DIMENSIONS	155(W) x 80(H) x 150(D)mm		
WEIGHT	Approx. 260g	Approx. 280g	Approx. 260g



PROFESSIONAL CCTV PRODUCTS SINCE 1978

**DISTRIBUIDO POR:**

**FABLET Y BERTONI SA.**

[www.topicacctv.com](http://www.topicacctv.com)

[www.topica.com.tw](http://www.topica.com.tw)