

## B/W BOX CAMERA

**TP-606B**    1/3" B/W CCD Camera  
**TP-608BK**    1/3" Low-cost B/W CCD Camera



### FEATURES:

- Attractive design of round camera case to fit the building
- Advanced circuit design for B/W camera in 480TV Lines(TP-606B) or 460 TV Lines (TP-608BK)
- Built-in Audio
- Advanced dual power design in compatible DC12V/AC24C and auto polarity
- Extreme low light capability at 0.04 Lux/F1.2(TP-606B) or 0.25 Lux/F1.2(TP-608BK)

SPECIFICATIONS		
MODEL	TP-606B	TP-608BK
<b>PICK-UP DEVICE</b>	1/3 " Interline Transfer CCD	
<b>SYNC SYSTEM</b>	Internal sync	
<b>PICTURE ELEMENTS</b>	EIA: 510(H)X492(V) CCIR: 500(H)X582(V)	
<b>SCANNING SYSTEM</b>	2:1 Interlace	
<b>SCANNING FREQUENCY</b>	EIA: H:15.734 Khz V: 60Hz CCIR: H:15.625 Khz V: 50Hz	
<b>HORIZONTAL RESOLUTION</b>	480 TV Lines	460TV Lines
<b>S/N RATIO</b>	48 dB	
<b>MINIMUM ILLUMINATION</b>	0.04LUX/F1.2	0.25LUX/F1.2
<b>ELECTRONIC SHUTTER</b>	1/60(1/50) to 1/100,000(1/110,000) sec.	
<b>IRIS CONTROL</b>	Video/Direct Drive Auto Iris switch	
<b>LENS MOUNT</b>	CS Mount or C Mount with 5mm adaptor ring	
<b>BACK LIGHT COMPENSATION</b>	On/off switch	
<b>AUDIO</b>	Built-in high sensitive microphone	
<b>VIDEO OUTPUT</b>	1.0 Vp-p, 75 ohm	
<b>POWER SOURCE</b>	DC12V ± 10% or DC12V/AC24V or AC/110V/220V	
<b>POWER CONSUMPTION</b>	APPROX. 3.3W(including auto iris power consumption)	
<b>STORAGE TEMPERTURE</b>	-40 to +60	
<b>OPERATING TEMPERTURE</b>	-10 to +60	
<b>DIMENSIONS</b>	58(W)x50(H)x106(D)mm	
<b>WEIGHT</b>	DC TYPE: 270 g DC/AC: 500 g AC TYPE: 500 g	