

COVERT CAMERA

TP-902PIR

1/3" B/W CCD Camera with Working PIR, Pinhole Lens

TP-902DM

1/3" B/W CCD Camera with Dummy PIR, Pinhole Lens



FEATURES:

- Covert Camera with PIR Case
- B/W camera with Working or Dummy PIR
- With built-in 5.5mm Pinehole Lens at F2.0

SPECIFICATIONS

MODEL	TP-902PIR	TP-902DM
PICTURE ELEMENTS	EIA: 510(H)x492(V) CCIR: 500(H)x582(V)	
SYNC FREQUENCY	EIA: H: 15.734 KHz V: 60 Hz CCIR: H: 15.625 KHz V: 50 Hz	
CLOCK FREQUENCY	19.0699 MHZ 18.937 MHZ	
IMAGE SIZE	6.3(H) x 5.4(V) mm	
UNIT CELL SIZE	9.8(H) x 6.3(V) mm	
SYNCHRONIZATION	Internal	
SCANNING SYSTEM	2:1 Interlace	
HORIZONTAL RESOLUTION	380 TV Lines	
LENS MOUNT	5.5mm Pinehole Lens /F2.0	
AUDIO	Optional	
MINIMUM ILLUMINATION	0.5LUX	
S/N RATIO	More than 46 dB(AGE off)	
AUTO GAIN CONTROL	Automatically	
GAMMA CORRECTION	0.45	
ELECTRONIC SHUTTER	1/60(1/50) to 1/100,000(1/110,000) SEC Linear	
VIDEO OUTPUT	Composite 1.0 Vp-p, 75 ohm	
POWER SOURCE	DC12V \pm 10%	
POWER CONSUMPTION	110mA Max.	
STORAGE TEMPERTURE	-20 to +60	
DIMENSIONS	70(W) x 120(H)x 43(D)mm	
WEIGHT	125g	100g

DISTRIBIDO POR:

FABET Y BRTONI SA.