

IR INTEGRATED CAMERAS

- TP-936WIR-SP** 1/3" Weather-proof D/N IR Camera with 4.3mm Fixed Lens
TP-936WIR-WC 1/3" Weather-proof D/N IR Camera with 4.3mm Fixed Lens
TP-936WIR-MSP 1/3" Low Budget Compact Size D/N IR Camera with 3.6mm Fixed Lens

TP-936WIR-SP
 TP-936WIR-



TP-936WIR-

FEATURES:

- With weather-proof IP66 housing and sunshield cover
- With built-in 4.3mm fixed lens / F2.0 (TP-936WIR-SP, TP-936WIR-WC)
- With 12 IR LED for night viewing range from 10~20M (TP-936WIR-SP, TP-936WIR-WC)
 or With 18 LED for night viewing range from 15~20M (TP-936WIR-MSP)

SPECIFICATIONS

| MODEL | TP-936WIR-WC | TP-936WIR-SP | TP-936WIR-MSP |
|-------------------------|---|--------------|-----------------------------|
| PICK-UP DEVICE | 1/3" Interline Transfer CCD | | |
| SYNC SYSTEM | Internal sync. | | |
| SCANNING SYSTEM | 2:1 Internal | | |
| PICTURE ELEMENTS | NTSC: 512(H)X492(V) PAL: 512(H)X582(V) | | |
| HORIZONTAL RESOLUTION | 420 TV Lines | | |
| LENS | 4.3mm / F2.0 | | 4.3mm / F2.0 |
| MINIMUM ILLUMINATION | 0.1 LUX / F1.2 (IR on 0 Lux) | | |
| AUTO WHITE BALANCE | Multi-Color Temperature(MCT) | | |
| BACK LIGHT COMPENSATION | Full Auto | | |
| AUTO GAIN CONTROL | Full Auto | | |
| GAMMA CORRECTION | 0.45 | | |
| ELECTRONIC SHUTTER | Auto and up to 1/100,000(1/110,000) sec. | | |
| S/N RATIO | Over 48dB | | |
| VIDEO OUTPUT | 1.0Vp-p, 75ohm | | |
| IR LED | 850nm x 12 | | 850nm x 18 |
| EFFECTIVE VISUAL RANGE | 10~20M | | 15~20M |
| WATERPROOFING CRITERION | IP66 | | |
| POWER CONSUMPTION | 150mA ± 10% IR 90mA ± 10% under DC12V | | |
| POWER SOURCE | DC 12V ± 10% | | |
| WORKING TEMPERATURE | -10 to +45 | | |
| DIMENSIONS | 53(Φ) x 74(L)mm | | 52(Φ) x 61(L)mm |
| WEIGHT | Approx. 336g (with bracket) | | Approx. 262g (with bracket) |

DISTRIBUIDO POR:

FABLET Y BERTONI S.A.

www.topicacctv.com

www.topica.com.tw

TOPICA
 PROFESSIONAL CCTV PRODUCTS SINCE 1978