

## TEST MONITOR KIT

### TP-56CCTFT 5.6" TFT LCD MONITOR, CARRYING CASE WITH RECHARGABLE BATTERY



#### FEATURES:

- 5.6" TFT full screen color monitor
- With portable carrying bag, rechargeable battery and signal cable for installation application
- Easy adjustment for installation in all kinds of locations
- User-friendly operation interface
- Built-in Audio

#### SPECIFICATIONS

|                              |                                       |
|------------------------------|---------------------------------------|
| <b>SCREEN SIZE</b>           | 5.6", 116(H) x 87(V) mm               |
| <b>ACTIVE AREA</b>           | 111.36(H) x 83.52(V) mm               |
| <b>DRIVE SYSTEM</b>          | A-Si TFT active matrix                |
| <b>SCREEN COLOR</b>          | Full color                            |
| <b>RESOLUTION</b>            | 320(H) xRGBx 240(V) dos               |
| <b>DOT PICH</b>              | 0.116(H)x0.348(V)                     |
| <b>CONTRAST RATIO</b>        | 85:1                                  |
| <b>BRIGHTNESS</b>            | 270 cd/m2                             |
| <b>SOUND OUTPUT</b>          | 200mW, built-in 4cm speaker x 1       |
| <b>INPUT TERMINALS</b>       | Power input, Video input, Audio input |
| <b>POWER INPUT</b>           | DC 9V~20V, Pin 2.0                    |
| <b>VIDEO INPUT</b>           | 0.75 Vp-p~1 Vp-p, Pin 2.0             |
| <b>AUDIO INPUT</b>           | 50mV(min), Stereo in, Pin 3.5         |
| <b>STEREO OUTPUT</b>         | Ear phone, pin 3.5                    |
| <b>SCREEN DISPLAY</b>        | Reverse/Normal switchable             |
| <b>POWER SOURCE</b>          | DC 12V $\pm$ 10%/600mA                |
| <b>POWER CONSUMPTION</b>     | 8W(max)                               |
| <b>OPERATION TEMPERATURE</b> | -40 to +95                            |
| <b>DIMENSIONS</b>            | 133(W) x 162(H) x54(D) mm             |

DISTRIBUIDO POR:

FABLET Y BERTONI S.A.